

digiled MC7 - 7mm Outdoor Blow-Through LED Panel





When your designs require blow through video displays, dynamic video backdrops, or vibrant lighting effects the digiLED MC7 is the right choice to give your designs visual impact. The 7mm pixel pitch of the MC7 allows for crisp high definition imagery paired with the ability to allow light, audio, or effects to pass through the LED screen. With its 12% transparency, the high-resolution MC7 screens can deal with higher speed winds over any other high resolution LED video screen. With a range a of hanging or stacking options as well as touring frames, this LED video product provides the dynamic looks that make your designs stand out.

Further enhancing the user experience and reliability of the digiLED MC7 LED Module is the NovaStar processing for precise module-to-module calibration that ensures accurate color matching for an overall excellent image. The LED product maintains full 16-bit depth whatever the brightness, for images free of contouring and quantizing, with perfect greyscale transition.

Optical

Pixel Configuration 3-in-1 SMD Pixel Pitch 7.812mm Pixel Resolution (module) 64 x 64 Pixel Density (m2) 16,384 pixels **Brightness** ≥6,500 cd/m2 Minimum Viewing Distance 7m (23') Viewing Angle H: 160° / V: 120° Gray Scale (Maximum) 16 Bit

Physical

500mm / 19.69" Module Height 500mm / 19.69" Module Width 116mm / 4.6" Module Depth .25sqm / 2.69sqft Module Area 9.45kg / 20.8lbs Module Weight 37.8kg / 83.3lbs Module Weight per m2 N/A Maximum modules hung N/A Maximum modules stacked 12% Transparency

Environmental

Indoor/Outdoor
Input Voltage
Average Power Consumption
Max. Power Consumption
Power Connector
Ingress Protection Rating
Temperature Range
Humidity
Average No-Failure Time
Life Span
Certification

Digital

Input source Refresh Rate Driving Method Control Distance Indoor or Outdoor 100V-240V AC 50/60 Hz 260W / m2 800W / m2 Neutrik Front: IP65 Back: IP54 -20°C to +45°C 10% to 90% Non-Condensing >10,000 Hours >100,000 Hours <0.00003 ETL,

DP, DVI and HDMI >1,380 Hz 1/7 Scan CAT5 Cable <100m;

FCC

CAT5 Cable <100m; Single Mode Fiber: <10km



Serving North America hello@ledtruckcompany.com www.ledtruckcompany.com